# Specification Sheet

# Topline SupaStadia

| | |
|---|---|
| What Is It? | A brilliant white water based emulsion line marking liquid. |
| What Does It Contain | Proprietary blend of inorganic pigment dispersion with binder resins for adhesion of the product to the applied surface. |
| Product Characteristics | Extremely flowable smooth, high density white emulsion based line marking liquid with excellent colour performance on dilution. |
| Colour Measurements | Whiteness Index min - 88 %<br>Dry Hiding Power min - 95.5 % |
| Typical Physical Properties | Wear resistance - Rating 8 - Excellent<br>Sedimentation - Rating 4 - Good<br>Weight per litre 1.32 kg<br>Viscosity Low / Medium |
| For Use On | Turf, red and gray shale, artificial turf |
| Recommended Dilution Rates<br>• Spray Marking | Initial marking 1 part S/S to 4 parts water<br>General marking 1 part S/S to 6 parts water<br>Over marking 1 part S/S to 8 parts water |
| • Transfer Wheel | Initial marking 1 part S/S to 1 parts water<br>General marking 1 part S/S to 3 parts water |
| Recommended For Use With | Topline TXE 252, 505<br>Topline Briteliner - Transfer Wheel Marker |
| Drying Time<br>(Dependant on air movement, humidity, dampness of substrate when applied) | Approximate:-<br>Warm 20°C and above 3 - 5 mins<br>Cool 10°C to 20°C 5 - 15 mins<br>Cold 1°C to 10°C 15 - 60 mins |