




NEW
Reverse Start

MCV3100TS



Specifications

MCV3100TS Specifications

| | |
|------------------------------------|---------------------------|
| Handle Type | Top |
| Displacement | 30.1cc |
| Dimensions LxWxH | 262x237x214mm |
| Dry Weight* ¹ | 3.1kg |
| Max Output | 1.04kw |
| Guide Bar Type | 6 teeth sprocket nose bar |
| Guide Bar | 12inch |
| Fuel Tank Capacity | 0.24L |
| Chain Type | 91VG, 3/8inch |
| Chain Oil Tank Capacity | 0.18L |
| Chain Tension System | e-Just |
| Recoil Starting System | Reverse Start 2 |
| Vibration Level* ² | 4.6m/s ² |
| Sound Pressure Level* ³ | 98dB(A) |

*¹ Without guide bar and saw chain

*² Vibration Level on the handles measured according to ISO 22867 (m/s²)

*³ Sound Pressure Level measured according to ISO 22868

Versatile, lightweight and powerful
A high quality chainsaw that does the job.




e-Just

Our Patented e-Just chain tensioning system uses a ratchet mechanism on the front handle for quick chain tightening.



Reverse Start 2

Reverse Start 2 system incorporates the best features of an electric starter for fast and easy starts.



Hybrid Anti-Vibration System

Anti-vibration spring and rubber dampers ensures less vibration and easier operation for the user.



Pre-Vent System

Debris and saw dust are dispersed leaving only clean air running through the carburetor.