

BRUSH CUTTERS



NEW REVERSE Start
Reverse Start

BC5020H-RS
BC5020H-RS
BC5020H-RS



Specifications

BC5020H-RS Specifications

Dimensions (LxWxH)	1855x730x480 mm
Dry Weight	8.3kg
Engine	NE500 (49.9cc)
Output	1.91kw
Fuel tank	1.0L
Handle	Double
Recoil Starting System	Reverse Start 2
Drive Shaft	Solid steel ø8mm
Accessory (Blade)	3 teeth (255)
Accessory (Nylon head)	Semi-Auto (L)5
Harness	Double
Vibration Level* ¹	
Left Handle(Blade/Nylon)	4.8/7.5m/s ²
Right Handle(Blade/Nylon Head)	4.6/8.9m/s ²
Sound Pressure Level (Blade/Nylon Head)* ²	98.0/99.5dB(A)

*¹ Vibration Level on the handles measured according to ISO 22867 (m/s²)

*² Sound Pressure Level measured according to ISO 22868

Where ever you are, What ever the job.
 Make it a Maruyama Brush cutter.



Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration



Ergonomic Design Handle Grip

Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



High Torque Engine

MARUYAMA NE500 is engineered with high compression ratio resulting in higher torque and power.



Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.